

标题:TJC2509 系列连接器

Title: TJC2509 Connector

目录

Contents

1. 更改履历 Change record
2. 范围 Scope
3. 产品描述 Product description
4. 相关标准 Related standards
5. 参数范围 Parameter ratings
6. 产品性能 Performance
7. 测试分组 Test sequences

中国·浙江省乐清市虹桥镇幸福东路 1098 号
合兴工业园
1098, Xingfu `Road(East), CWB Industrial Zone, Hongqiao,
Yueqing, Zhejiang 325608, China
Tel: 86-577-61313157(Research & Development Dept.)
Tel: 86-577-62312253(Sales Dept.)

制定 Edit:
路 欢 2021.08.25

审核 Check:
王曲 2024.3.4

批准 Approval:
刘冬旭 2024.3.4

产品名称 Product name:
TJC2509 系列连接器

编号 Document No.:
PS4100

版本 Revision:
V28

1. 更改履历 Change record

版本号 Version No.	更改前描述 Description before modification	更改后描述 Description after modification	更改人/日期 Reviser/Date		
V0	/	初版发行 First release	路欢 2021/08/25 Huan.Lu 2021/08/25		
V1	/	根据新的命名规范更新规格型号 Update specifications and part no according to new naming specifications	尹恒 2022/03/12 Heng.Yin 2022/03/12		
V2	/	新增 TJC2509-nAR/nARP 产品 Added TJC2509-nAR/nARP products	路欢 2022/04/20 Huan.Lu 2022/04/20		
V3	/	新增 CH-TJC2509-2 端子 Added CH-TJC2509-2 contact	尹恒 2022/05/20 Heng.Yin 2022/05/20		
V4	/	新增 TJC2509-2×Nad,TJC2509-2×nY,CH-TJC2509-L 系列等产品 TJC2509-2×nAD,TJC2509-2×nY,CH-TJC2509-L series are added	尹恒 2022/07/11 Heng.Yin 2022/07/11		
V5	/	TJC2509 阳连接器材料更新,更新导线线号名称,新增 TJC2509-7/8AT 产品 TJC2509 male connector material updated, updated wire number name, new TJC2509-7/8AT product	尹恒 2022/07/22 YinHeng 2022/07/22		
V6	/	针固定力更新,CH-TJC2509-1 适用绝缘外径更新 Needle fixing force update, CH-TJC2509-1 applicable insulation diameter update	尹恒 2022/07/28 Heng.Yin 2022/07/28		
V7	/	新增 TJC2509E-5AWJDK 产品 Added TJC2509E-5AWJDK product	尹恒 2022/08/04 Heng.Yin 2022/08/04		
V8	/	新增 TJC2509-14ARP/CZ-TJC2509-1 产品 Added TJC2509-14ARP/CZ-TJC2509-1 product	路欢 2022/08/17 Huan.Lu 2022/08/17		
V9	/	根据企标更新抗张强度 Update tensile strength according to enterprise standard	尹恒 2022/08/29 Heng.Yin 2022/08/29		
V10	/	更新使用温度范围 Update the operating temperature range	尹恒 2022/10/10 Heng.Yin 2022/10/10		
V11	/	删除命名规则内不可量产的材料 Delete material that cannot be mass-produced in a naming convention	王曲 2023/04/03 Qu.Wang 2023/04/03		
V12	/	插簧固定力由 15N 改为 20N The fixing force of the spring is changed from 15N to 20N	胡杰斌 2023/05/27 Jiebin.Hu 2023/05/27		
V13	/	根据客户要求更新生产地, 生产工厂等信息 Update production location, production plant and other information according to customer requirements	胡杰斌 2023/08/08 Jiebin,Hu 2023/08/08		
V14	/	新增线对线连接器材料信息无磷, 无溴 Added Material information No phosphorus, no bromine	胡杰斌 2023/08/17 Jiebin.Hu 2023/08/17		
V15	/	TJC2509 阳连接器新增粉色与紫色 TJC2509 Male connector added pink and purple	胡杰斌 2023/10/23 Jiebin.Hu 2023/10/23		
V16	/	CZ-TJC2509 增加 AWG#26 线型 CZ-TJC2509 Added AWG#26 lines	徐秋秋 2023/11/22 Qiuqiu.Xu 2023/11/22		
产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28

PAGE: 2 / 13

CWB						产品规格书		PRODUCT SPECIFICATION	
V17	/	新增 TJC2509B-2AD 阳连接器 Added the TJC2509B-2AD male connector				倪嘉伟 2024/01/31 Jiawei.Ni 2024/01/31			
V18	/	新增 TJC2509-2×5Y 孔座与 TJC2509-2×5YS 锁紧片 Added the TJC2509-2×5Y housing and TJC2509-2×5YS retainer				倪嘉伟 2024/03/04 Jiawei.Ni 2024/03/04			
V19	/	新增 TJC2509-2×5AD/TJC2509-2×7AD/ TJC2509-2×7Y/ TJC2509-2×7YS/ TJC2509-2×9YS 产品 Added TJC2509-2×5AD/TJC2509-2×7AD/ TJC2509-2×7Y/ TJC2509-2×7YS/ TJC2509-2×9YS products				倪嘉伟 2024/06/25 Jiawei.Ni 2024/06/25			
V20	/	更新 TJC2509-2×nYS 产品型号 Updated TJC2509-2 x nYS product model				倪嘉伟 2024/07/18 Jiawei.Ni 2024/07/18			
V21	/	CH-TJC2509 倒角高度尺寸增加公差管控 CH-TJC2509 chamfer height dimension increase tolerance control				徐秋秋 2024/08/06 Qiuqiu.Xu 2024/08/06			
V22	/	CZ-TJC2509 增加 1.0mm 线径的导线 CZ-TJC2509 Added 1.0mm wire diameter				徐秋秋 2024/08/23 Qiuqiu.Xu 2024/08/23			
V23	/	通用版规格书插簧固定力有 20N 改为 15N The fixing force of the spring in the general version specification is changed from 20N to 15N				胡杰斌 2024/09/12 Jiebin.Hu2024/09/12			
V24	/	命名规则更新 Naming convention update				徐秋秋 2024/09/20 Qiuqiu.Xu 2024/09/20			
V25	/	TJC2509-nARP 曾用规格纠错 TJC2509-nARP has used specifications for error correction				徐秋秋 2024/11/20 Qiuqiu.Xu 2024/11/20			
V26	/	新增 TJC2509B-2×5AD 阳连接器；命名规则深色描述纠错 Added the TJC2509B-2×5AD Header; Naming Rule Dark Description Error correction				倪嘉伟 2024/11/29 Jiawei Ni 2024/11/29			
V27	/	更新 CH-TJC2509-L 图纸，型号和对应的适用线型 Updated CH-TJC2509-L drawings, models and corresponding applicable lines				倪嘉伟 2024/12/13 Jiawei Ni 2024/12/13			
V28	/	新增 TJC2509-2×6AD 阳连接器 Add the TJC2509-2×6AD Header				倪嘉伟 2025/5/13 Jiawei Ni 2025/5/13			
2. 适用范围 Scope									
本产品规格书适用于浙江合兴电子元件有限公司生产的 WTB&WTW 2.5 阴型 & 阳型电子连接器，产品名称:TJC2509 系列连接器。									
This product specification covers the requirement for wire to board(wire) 2.5mm pitch Receptacle & Plug connector, which is designed and manufactured by CWB Electronics(ZheJiang) Co.,LTD. P/N: TJC2509 Connector.									
3. 产品描述 Product description									
TJC2509 系列连接器产品为家电连接器产品，产品部件组成如下：									
The TJC2509 series connector designed for home appliances connection. part checklist as following form:									
零件名称 Part name		规格型号 Part No.		曾用规格型号 Previous part No.		描述 Description		备注 Remark	
孔座（含锁紧片保持结		TJC2509-nY(**-*)		TJC2509-nY		PA66 UL94V-0		Red Phosphorus free,	
产品名称 Product Name:		TJC2509 系列连接器		编号 Document No.		PS4100		版本号 Version No.	
								V28	
PAGE: 3 / 13									



产品规格书

PRODUCT SPECIFICATION

构) Housing(W/Retainer)				Brominate free
孔座 (含锁紧片保持结构) Housing(W/Retainer)	TJC2509-2×nY(**-*)	/	PA66 UL94V-0	Red Phosphorus free, Brominate free
孔座 (含锁紧片保持结构, 带外锁扣)	TJC2509B-nY* (**-*)	TJC2509B-nY	PA66 UL94V-0	Red Phosphorus free, Brominate free
Housing (W/Retainer, W/Lock)			PA66 UL94V-0 GWT750℃	Red Phosphorus free, Brominate
锁紧片 Retainer	TJC2509B-nS* (**-*)	TJC2509-nYS	PA66+GF UL94V-0 GWT750℃	Red Phosphorus free, Brominate
锁紧片 (双排) Retainer(Double rows)	TJC2509-2×nYS* (**-*)	/	PA66+GF UL94V- 0 GWT750℃	Red Phosphorus free, Brominate
插簧 Contact	CH-TJC2509-**	CH-TJC2509	AWG#24~AWG#22	/
插簧 Contact	CH-TJC2509-1-**	CH-TJC2509-1	AWG#28~AWG#26	/
插簧 Contact	CH-TJC2509-2-**	CH-TJC2509-2	AWG#20	/
插簧 Contact	CH-TJC2509-L-**	/	AWG#24~AWG#20	/
插簧 Contact	CH-TJC2509-1-L-**	/	AWG#28~AWG#26	/
插针 Pin contact	CZ-TJC2509-1-**	/	AWG#20	/
插针 Pin contact	CZ-TJC2509-**	CZ-TJC2509-D	AWG#26~AWG#22	/
阳连接器 (立式, 直插, 含小弯) Header(V, DIP, W/Kink)	TJC2509-nAK *(**-*)	TJC2509-nA	Wafer: PA66 +GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器 (立式, 直插, 含小弯) Header(V, DIP, W/Kink)	TJC2509-nAK-1 *(**-*)	TJC2509-nA-1	Wafer: PA66 +GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器 (立式, 直插, 含定位柱, 含小弯) Header(V, DIP, W/Boss, W/Kink)	TJC2509-nADK *(**-*)	TJC2509-nAD	Wafer: PA66+GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器 (立式, 直插, 含定位柱) Header(V, DIP, W/Boss,)	TJC2509B-2AD *(**-*)	/	Wafer:PA66+GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器 (立式, 直插, 含定位柱) Header(V, DIP, W/Boss)	TJC2509-2×nAD *(**-*)	/	Wafer:PA66+GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器 (立式, 直插, 含定位柱) Header(V, DIP, W/Boss)	TJC2509B-2×5AD *(**-*)	/	Wafer:PA66+GF UL94V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
-----------------------	---------------	--------------------	--------	--------------------	-----

阳连接器（卧式，直插，含挡板） Header(H, DIP, W/PCB stabilizer)	TJC2509-nAWJ ***-*	TJC2509-nAWJ	Wafer: PA66+GF UL94 V-0 GWT750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器（卧式，直插，含小弯，含挡板） Header(H, DIP, W/Kink, W/PCB stabilizer)	TJC2509-nAWJK ***-*	TJC2509-nAWJ-1	Wafer: PA66+GF UL94 V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器（卧式，直插，含挡板，带倒钩） Header(H, DIP, W/PCB stabilizer, W/Boss)	TJC2509-nAWJD ***-*	TJC2509-nAWDJ	Wafer: PA66+GF UL94 V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器（卧式，直插，含小弯，含挡板，含倒钩） Header(H, DIP, W/Kink, W/PCB stabilizer, W/Boss)	TJC2509-nAWJDK ***-*	TJC2509-nAWDJ-1	Wafer: PA66+GF UL94 V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器（卧式，直插，含小弯，含挡板，含倒钩） Header(H, DIP, W/Kink, W/PCB stabilizer, W/Boss)	TJC2509E-5AWJDK ***-*	/	Wafer: PA66+GF UL94 V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
阳连接器（立式，直插） Header(V, DIP)	TJC2509-nAT***-*	TJC25054-nA	Wafer: PA66+GF UL94 V-0 GWT 750℃ Post: Brass, tin plated	Red Phosphorus free, Brominate
条形连接器孔座(含锁紧片保持结构) Receptacle housing (Retainer mountable type)	TJC2509-nAR***-*	TJC2509-nAP	PA66 UL94 V-0	Red Phosphorus free, Brominate free
条形连接器针座(面板安装，含锁紧片保持结构) Receptacle housing(Panel mount, Retainer mountable type)	TJC2509-nARP***-*	TJC2509-nAR-1	PA66 UL94 V-0	Red Phosphorus free, Brominate free

4.相关标准 Related standards

以下参考文件是本规格书的一个组成部份。若本规格书中的要求与产品图纸发生冲突，以产品图中的要求为优先；若本规格书中的要求与参考文件中的要求冲突，以本规格书要求为优先。

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
-----------------------	---------------	--------------------	--------	--------------------	-----

The following documents form a part of this specification. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.

GB/T 2421 环境试验 概述和指南

Environmental testing — General and guidance

GB/T 2423 环境试验 试验方法

Environmental testing — Test methods

GB/T 2424 环境试验 支持文件及导则

Environmental testing — Supporting documentation and guidance

GB/T 5095 电子设备用机电元件基本试验规程及测量方法

Electromechanical components for electronic equipment Basic testing procedures and measuring methods

EIA-364 EIA-364 系列标准

EIA-364 series standards

IPC EIA IPC JEDEC J STD 002E 连接器 / 插座终端可焊性测试方法

Solderability Tests for Component Leads, Terminations, Lugs, Terminals and Wires

产品符合 RoHS 标准。





The product should comply with RoHS.

5. 参数范围 Parameter ratings:




额定电流 [AC(有效值)/DC] Rated current [AC(rms)/DC]	AWG#28	AWG#26	AWG#24	AWG#22	AWG#20
	1.0A	1.5A	2.5A	3.0A	4.0A
适用 PCB 板 Applicable PCB	Board thickness: 1.6mm Hole diameter: $\phi 0.85\text{mm} \sim \phi 0.95 \text{ mm}$ Hole diameter: $\phi 1.1\text{mm} \sim \phi 1.2 \text{ mm}$ (TJC2509-nAT)				
额定电压[AC(有效值)/DC] Rated voltage [AC(rms)/DC]	250V				
使用温度范围 (包含温升) Operating temperature range (include temperature rise)	$-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$				
适用线型 (具体适用线型请参考压接规格书) Applicable wires (Please refer to the crimping specification for details)	CH-TJC2509	Wire size: AWG#24~AWG#22 ($0.2\text{mm}^2 - 0.33\text{mm}^2$) Insulation diameter: $\phi 1.4\text{mm} - \phi 1.6\text{mm}$			
	CH-TJC2509-L	Wire size: AWG#24~AWG#20 ($0.2\text{mm}^2 - 0.52\text{mm}^2$) Insulation diameter: $\phi 1.4\text{mm} - \phi 1.9\text{mm}$			
	CH-TJC2509-1/ CH-TJC2509-1-L	Wire size: AWG#28~AWG#26 ($0.08\text{mm}^2 - 0.14\text{mm}^2$) Insulation diameter: $\phi 0.92\text{mm} - \phi 1.44\text{mm}$			
	CH-TJC2509-2	Wire size: AWG#20 (0.52mm^2) Insulation diameter: $\phi 1.75\text{mm} - \phi 1.9\text{mm}$			
	CZ-TJC2509-1	Wire size: AWG#20 (0.52mm^2) Insulation diameter: $\phi 1.75\text{mm} - \phi 1.9\text{mm}$			
	CZ-TJC2509	Wire size: AWG#26~AWG#22 ($0.14\text{mm}^2 - 0.33\text{mm}^2$) Insulation diameter: $\phi 1.0\text{mm} - \phi 1.6\text{mm}$			
产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28

6. 产品性能 Performance

6.1 机械性能 Mechanical

序号 No.	项 目 Item	测试条件 Test condition	规 格 Requirement		
6.1.1	外观 Appearance	目测 Checking by eyes 视力: 1.0 以上 Eyesight: > 1.0 照明: (200~300) lx Lamp: (200~300) lx 目测距离: (0.3~0.5) m Space: (0.3~0.5) m GB/T 5095.2 Method 1a	1.塑料件表面应无明显疤痕、凹陷、开裂及影响使用的变形。 Plastic part: smooth and flat surface without discolor, broken, crack, and distortion, etc. 2 金属件表面无锈蚀、氧化 、无明显的机械损伤及电镀层脱落等缺陷。 Metal part: bright and even surface without rust, oxide, fog and obvious physical damage, etc.		
6.1.2	端子插入力与 固定力 Insertion force and retention force for contact	应测量将端子沿轴线方向插入孔座和拔出孔座的力, 测试速度不大于25 mm/min。 The force of inserting and pulling the contact into and out of the housing along the axis shall be measured (Testing speed: <25 mm/min.) GB/T 5095.8 Method 15d / EIA-364-29B (不带锁紧片)  (带锁紧片) 	插入力 (Insertion) Max.	固定力(不带锁紧片测试) Retention (Test without locking plate) Min.	固定力 (带锁紧片测试) Retention (Test with locking plate) Min.
6.1.3	插簧与插针的 插拔力 Insertion and withdrawal force for Pin in the contact	固定连接器和/或测力计, 在端子轴线方向将插针插入和拔出插簧, 测试速度不大于 25 mm/min。 Insert the pin contact into and pull out the socket contact in the direction of the terminal axis (Testing speed: <25 mm/min.) GB/T 5095.7 Method 13b / EIA-364-13B 	插入力 (Insertion force) Max.	拔出力(Withdrawal force) Min.	
			9.8N	0.2N	
6.1.4	针的固定力 Post retention force	沿插针轴线方向施加推力,测量将插针从塑件上分离的力, 测试速度不大于 25 mm/min。(不包括 TJC2509-nAR/ nARP) The end of a post shall be pushed in a direction perpendicular to a wafer. The load required to make the post start moving from the wafer shall be measured. (Testing speed: <25 mm/min.) (exclude TJC2509-nAR/ nARP) GB/T 5095.8 Method 15a / EIA-364-29B 	TJC2509-2AK~4AK(Bossed Contact Pin): 50N Min. Others: 20N Min.		

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
-----------------------	---------------	--------------------	--------	--------------------	-----

6.1.5	压着部位抗张强度 Crimp tensile strength	在已压接端子的头部和导线上施加拉力，并测量将导线从端子拉出或导线断裂所需的力，测试速度不大于 25 mm/min。 Pulling load shall be applied to a correctly crimped contact and a wire. The load required to pull the wire out of the contact or break the wire shall be measured. (Testing speed: <25 mm/min.) GB/T5095.8 Method 16d / EIA-364-08B 	AWG#28: 8.9N Min. AWG#26: 13.4N Min. AWG#24: 22.3N Min. AWG#22: 35.6N Min. AWG#20: 57.9 N Min.			
6.1.6	锁扣强度 Lock strength	固定连接器和测力计，在连接器轴线方向将配合后的连接器拔出，速度不大于25 mm/min.，测量时连接器应无端子或端子不影响锁扣强度的测量结果 Apply axial withdraw force on the connector which without contact or the contacts shall not affect lock strength at a rate less than 25 mm/min. GB/T 5095.8 Method 15f / EIA-364-29B 	2pin: 20N Min. 3pin~16pin: 30N Min.			
6.1.7	成品插入力与拔出力（去锁扣） Insertion force and withdrawal force (without lock)	将装有已压接端子的孔座与阳连接器做插入和拔出，测量首次插入力、首次拔出力及第30次拔出力，测试速度不大于25 mm/min。 注：单排阴连接器需使用CH-TJC2509系列端子进行测试；双排阴连接器需使用CH-TJC2509-L系列端子进行测试。 A housing with crimped contacts and a header shall be mated and unmated on the mating axis. Initial insertion and withdrawal forces and withdrawal force at 30th shall be measured. (Testing speed: <25 mm/min.) Note: The single row housing should be tested with CH-TJC2509 series contact. The two rows housing should be tested with CH-TJC2509-L series contact. GB/T 5095.7 Method 13b / EIA-364-13B 	No. of Poles. 极数	插入力（最大值） Insertion (Max.) 初次 1st.	拔出力（最小值） Withdrawal (Min.) 初次 1st. 第三十次 30th.	
			2P	20N	1.1N	0.8N
			3P	25N	1.5N	1.0N
			4P	30N	2.0N	1.2N
			5P	35N	2.5N	1.5N
			6P	40N	3.0N	2.0N
			7P	45N	3.5N	2.5N
			8P	50N	4.0N	3.0N
			9P	55N	4.5N	3.5N
			10P	60N	5.0N	4.0N
			11P	65N	5.5N.	4.5N
			12P	70N	6.0N	5.0N
			13P	75N	6.5N	5.5N
			14P	80N	7.0N	6.0N
			15P	85N	7.5N	6.5N
			16P	90N	8.0N	7.0N
			2×5P	45N	5.0N	4.0N
			2×5P	54N	6.0N	5.0N
2×7P	63N	7.0N	6.0N			
产品名称 Product Name:		TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28

PAGE: 8 / 13

			2×9P	81N	9.0N	8.0N
			2×10P	90N	10.0N	9.0N
			2×11P	99N	11.0N	10.0N
			2×14P	126N	14.0N	13.0N
			2×17P	153N	17.0N	16.0N
			2×18P	162N	18.0N	17.0N
6.1.8	机械振动 Vibration	插合连接器, 串联在直流电源上, 电流100mA; 并模拟正常工作状态: 振频为 (10~55~10) Hz, 每个循环时间为1分钟, 振幅1.52mm。沿XYZ三轴正反方向各循环2小时 Mate connectors subjected them to following vibration conditions, for a period of 2 hours in each of 3 mutually perpendicular axes, 100 mA current shall be applied. Frequency: (10~55~10)Hz/min. Cycling time: 1 min. Amplitude: 1.52mm. GB/T 5095.4 Method 6d / EIA-364-28D	外观: 无损伤 (参照6.1.1) Appearance: no damage.(refer to 6.1.1) 接触电阻: 20mΩ Max. Contact resistance: 20mΩ Max. 电流中断时间: 1μsec Max. Current interruption: 1μsec Max.			
6.1.9	机械冲击 Shock	连接器相配, 沿XYZ三轴正反方向各冲击3次(总共18次), 在测试过程中通以100mA电流 冲击强度: 490m/s ² 持续时间: 11ms Mate connectors and subject them to the following shock conditions, 3 times of shock shall be applied for each 6 directions along 3 mutually perpendicular axes, passing DC 100mA current during the test.(total of 18 shocks) Test pulse: 490m/s ² Duration: 11ms GB/T 5095.4 Method 6c / EIA-364-27B	外观: 无损伤 (参照6.1.1) Appearance: no damage.(refer to 6.1.1) 电流中断时间: 1μsec Max. Current interruption: 1μsec Max.			
6.1.10	机械寿命 Durability	以每分钟 10 次的速度插拔 50 次 50 cycles for mating and unmating test at the speed of 10 cycles per minute GB/T 5095.5 Method 9a / EIA-364-09C	外观: 无损伤 (参照6.1.1) Appearance: no damage.(refer to 6.1.1) 接触电阻: 20mΩ Max. Contact resistance: 20mΩ Max.			

6.2 电气性能 Electrical

序号 No.	项 目 Item	测试条件 Test condition	规格 Requirement
6.2.1	接触电阻 Contact resistance	插配阴阳连接器后, 用小功率电路进行测试 Mate connectors with dry circuit to test contact resistance GB/T 5095.2 Method 2a / EIA-364-23B	10mΩ Max. (Initial) 20mΩ Max. (Final)
6.2.2	绝缘电阻 Insulation resistance	在相邻接触件之间或地线之间, 用 500V DC 电压进行测试 Apply a voltage of 500V DC between adjacent contacts and between contacts to ground. GB/T 5095.2 Method 3a / EIA-364-21C	1000 MΩ Min. (Initial) 500 MΩ Min. (Final)

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
PAGE: 9 / 13					

6.2.3	耐电压 Withstand voltage	相邻接触件之间或地线之间施加 1000V AC（有效值），漏电流 1mA 的电压作用,时间 1min. Apply a voltage of 1000V AC (rms) and leakage current of 1mA between adjacent contacts or ground cables for 1 minute. GB/T 5095.2 Method 4a / EIA-364-20B	外观：无击穿和飞弧现象 Appearance: no breakdown or flashover
6.2.4	温升 Temperature rise	插合连接器，通以最大允许电流，测温度的差值 Mate connectors and measure the temperature rise of contact when the maximum AC rated current is passed. GB/T 5095.3 Method 5a / EIA-364-70A	$\Delta 30^{\circ}\text{C}$ Max.

6.3 环境性能 Environmental

序号 No.	项 目 Item	测试条件 Test condition	规 格 Requirement										
6.3.1	耐高温 Heat resistance	连接器配合后，于（105±2）℃的空气中放置 240 小时，再回到室温中放置（1~2）小时测定 Mated connectors exposed to the condition of (105±2)℃ for 240 hours, recovery time (1~2) hours GB/T 5095.6 Method 11i / EIA-364-17B	外观：无损伤（参照6.1.1） Appearance: no damage.(refer to 6.1.1) 接触电阻：20mΩ Max. Contact resistance: 20mΩ Max. 绝缘电阻：500 MΩ Min. Insulation resistance: 500 MΩ Min. 耐电压：1000V Min. Withstand voltage: 1000V Min.										
6.3.2	耐低温 Cold resistance	连接器配合后，于（-40±2）℃的空气中放置 96 小时，再回到室温中放置（1~2）小时测定 Mated connectors exposed to the condition of (-40±2)℃ for 96hours, recovery time (1~2) hours GB/T 5095.6 Method 11j / EIA-364-17B	外观：无损伤（参照6.1.1） Appearance: no damage.(refer to 6.1.1) 接触电阻：20mΩ Max. Contact resistance: 20mΩ Max. 绝缘电阻：500 MΩ Min. Insulation resistance: 500 MΩ Min. 耐电压：1000V Min. Withstand voltage: 1000V Min.										
6.3.3	恒定湿热 Humidity	温度（40±2）℃ 相对湿度（90~95）% 搁置时间 240 小时，取出恢复（1~2）小时后检查。 Mated connectors exposed to the condition of temperature (40±2)℃, humidity (90~95)% for 240 hours, recovery time (1~2) hours GB/T 5095.6 Method 11c /EIA-364-31B	外观：无损伤（参照6.1.1） Appearance: no damage.(refer to 6.1.1) 接触电阻：20mΩ Max. Contact resistance: 20mΩ Max. 绝缘电阻：500 MΩ Min. Insulation resistance: 500 MΩ Min. 耐电压：1000V Min. Withstand voltage: 1000V Min.										
6.3.4	温度循环 Temperature cycling	把试验样品分别放入高、低温试验箱中，按下列步骤调试验温度： a) 在（-55±2）℃的恒温条件下放置 0.5 小时； b) 在（85±2）℃的恒温条件下放置 0.5 小时； 从 a)到 b)为一个循环，周期温度转换时间应不大于 5 分钟，共进行 25 个循环,恢复（1~2）小时后检查 Mated connectors shall be tested under the following conditions <table><tr><th>Temperature ℃</th><th>Duration</th></tr><tr><td>1 -55±2</td><td>0.5h</td></tr><tr><td>2 Room Temp.</td><td>5 minutes Max.</td></tr><tr><td>3 +85±2</td><td>0.5h</td></tr><tr><td>4 Room Temp.</td><td>5 minutes Max.</td></tr></table> Step 1 to 4 is one cycle,25 cycles shall be tested, recovery time (1~2) hours GB/T 5095.6 method 11d / EIA-364-32CGB/T	Temperature ℃	Duration	1 -55±2	0.5h	2 Room Temp.	5 minutes Max.	3 +85±2	0.5h	4 Room Temp.	5 minutes Max.	外观：无损伤（参照6.1.1） Appearance: no damage.(refer to 6.1.1) 接触电阻：20mΩ Max. Contact resistance: 20mΩ Max. 绝缘电阻：500 MΩ Min. Insulation resistance: 500 MΩ Min. 耐电压：1000V Min. Withstand voltage: 1000V Min.
Temperature ℃	Duration												
1 -55±2	0.5h												
2 Room Temp.	5 minutes Max.												
3 +85±2	0.5h												
4 Room Temp.	5 minutes Max.												

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
-----------------------	---------------	--------------------	--------	--------------------	-----

PAGE: 10 / 13

6.3.5	盐雾 Salt spray	把试验样品从试验箱顶悬挂下来,采用浓度为(5±1)% (质量百分比)的氯化钠溶液,在(35±2)℃温度下连续雾化48小时,试验后用流动的蒸馏水轻轻洗去表面沉积物。在常温常湿条件下恢复(1~2)小时 48 hours spray, at temp (35±2)℃, NaCl mist concentration (5±1)%. After test wash parts and put it into room ambient for (1~2) hours GB/T 5095.6 Method 11f /EIA-364-26B	外观:无损伤(五金件应无露出底金属的严重锈蚀;使用预镀好的型材,其落料面允许有不影响其性能的轻微腐蚀。) Appearance: no damage (no erosion on material exposed. and plating material, slight erosion on the cutting surface is acceptable) 接触电阻: 20mΩ Max. Contact resistance: 20mΩ Max.
6.3.6	工业气体(氨气) Industrial gas(Ammonia)(NH ₃)	连接器在每升容积内含25毫升3%氨溶液的氨气箱中暴露7小时 After 7 hours exposure in ammonia chamber with 25 mL of 3% ammonia solution for every liter of chamber capacity	无应力腐蚀开裂 No stress corrosion cracking
6.3.7	硫化氢气体测试 (H ₂ S gas test)	连接器配合后,在温度(40±2)℃、湿度(80±5)%、H ₂ S气体浓度为(3±1)ppm的环境中放置96小时 Mated connectors exposed to the condition of temperature (40±2)℃, humidity(80±5)%, H ₂ S gas concentration of (3±1)ppm for 96 hours	接触电阻: 20mΩ Max. Contact resistance: 20mΩ Max.
6.3.8	可焊性 Solderability	把试验样品需要焊接的部位浸入焊锡炉中,锡炉温度(245±5)℃,时间(4~5)秒。(不包括TJC2509-nAR/nARP) Dip solder tails into the molten solder held at (245±5)℃ for (4~5) seconds. (exclude TJC2509-nAR/ nARP) IPC EIA IPC JEDEC J STD 002E	上锡率≥95% Solder coverage: ≥95%
6.3.9	耐焊接热 Resistance to soldering heat	1.耐波峰焊热:把试验样品需要焊接的部位浸入焊锡炉中,锡炉温度(260±5)℃;时间(5±1)秒后,在正常条件下恢复(1~2)小时。(温度曲线见图1)(不包括TJC2509-nAR/nARP) Resistance to wave soldering heat: Dip solder tails into the molten solder held at (260±5)℃ for (5±1) seconds, recovery time (1~2) hours. (The temperature curve is shown in Figure 1) (exclude TJC2509-nAR/ nARP) 2.手工焊接:温度(350±10)℃,时间(1~2)s。(不包括TJC2509-nAR/nARP) Manual soldering: (350±10)℃ for (1~2) s. (exclude TJC2509-nAR/ nARP)	外观:无损伤(参照6.1.1) Appearance: no damage.(refer to 6.1.1)
6.3.10	灼热丝 Glow wire (只针对GWT750℃产品) Only for GWT750℃ product)	750℃灼热丝顶部接触试验样品, 接触时间:(30±1)s; 接近和离开速率:10mm/s~25mm/s; 灼热丝进入或贯穿试验样品深度:(7±0.5)mm。 750℃glow wire contacts with mated connector, Contact time: (30±1)s; Speed of closing to and leaving from: 10mm/s~25mm/s; Depth that glow wire penetrates mated connector:(7±0.5)mm. GB/T 5169.10	1.试验样品燃烧时间不超过2s。或 The time that mated connector burns should be not more than 2s.or 2、灼热丝离开后的30s内样件无火焰或灼热情况,且无滴落物或滴落物不燃烧。 Thirty seconds after glow wire leaves mated connector, it does not burn or have no incandescence and it does not fall something, or the falling thing does not burn.

产品名称
Product Name:

TJC2509 系列连接器

编号
Document No.

PS4100


版本号
Version No.

V28

产品规格书

PRODUCT SPECIFICATION

Pb-free Wave soldering Temperature profile



图中: $T_1 > 150^\circ\text{C}$ $T_2 > 220^\circ\text{C}$ $T_3 = 250^\circ\text{C} \pm 2^\circ\text{C}$ $T_4 > 230^\circ\text{C}$ $T_5 < 80^\circ\text{C}$
 $dT_1 < 5^\circ\text{C}$ $dT_2 < 15^\circ\text{C}$ $t_1 > 60\text{s}$ $t_2 + t_3 > 3\text{s} \sim 5\text{s}$ $T_3 - T_1 < 100^\circ\text{C}$

图 1 波峰焊曲线图

产品名称 Product Name:	TJC2509 系列连接器	编号 Document No.	PS4100	版本号 Version No.	V28
PAGE: 12 / 13					

8. 测试分组 Test sequences (Samples:5PCS)

测试组 Group number	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T
外观 Appearance	1	1	1	1	1	1	1, 5	1, 3	1, 7	1	1, 7	1, 5	1, 7	1, 7	1, 5	1, 3	1, 5	1, 3	1, 3	1
端子的插入力与固定力 Insertion force and retention force for contact	2																			
插簧与插针的插拔力 Insertion and withdrawal force for pin in the contact		2																		
针的固定力 Post retention force			2																	
压着部位抗张强度 Crimp tensile strength				2																
锁扣强度 Lock strength					2															
成品插入力与拔出力（去锁扣） Insertion force and withdrawal force(without lock)						2														
机械振动 Vibration							3													
机械冲击 Shock								2												
机械寿命 Durability									5											
接触电阻 Contact resistance							2, 4		2, 6		2, 4	2, 4	2, 4	2, 4	2, 4		2, 4			
绝缘电阻 Insulation resistance									3		5		5	5						
耐电压 Withstand voltage									4		6		6	6						
温升 Temperature rise										2										
耐高温 Heat resistance											3									
耐低温 Cold resistance												3								
恒定湿热 Humidity													3							
温度循环 Temperature cycling														3						
盐雾 Salt spray															3					
工业气体(氨气)Industrial gas(Ammonia)(NH ₃)																2				
硫化氢气体测试 (H ₂ S gas test)																	3			
可焊性 Solderability																		2		
耐焊接热 Resistance to soldering heat																			2	
灼热丝 Glow wire																				2

产品名称
Product Name:

TJC2509 系列连接器







编号
Document No.

PS4100

版本号
Version No.

V28

General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					








Notes:


- 1.Material: phosphor bronze, thickness=0.2mm
- 2.Surface finish: tin plated
- 3.Matched receptacle housing: TJC2509-nY/TJC2509B-nY/TJC25066-nY/TJC25067-nY
- 4.Applicable wires: CH-TJC2509 AWG#24 ~AWG#22
CH-TJC2509-1 AWG#28 ~AWG#26
CH-TJC2509-2 AWG#20
- 5.Compliant to the current RoHS

CUSTOMER DRAWING		CH-TJC2509-2		TJC2509-2		2.2	2.0	2.9	2.9
		CH-TJC2509-1		TJC2509-1		1.5	1.3	2.1	2.1
		CH-TJC2509		TJC2509		1.9	1.5	2.9	2.9
		Part.No		Previous part No.		A	B	C	D
		Dimension							
Title:						2.5mm pitch WTB/WTW contact			
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: CH-TJC2509-*.**		
Checked	Guoying.Wang	2022.3.16	mm	5:1	A4	B	Previous part No.: TJC2509/TJC2509-1		
			Sheet No.		1 Of 1				
Approved	Dongxu.Liu	2022.3.17	CWB				Document No.: CP-DWG-01135		
							Specification No.: PS4100/PS4159/PS4169		

General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



Contact view
1:2





Notes:

- 1.Material: phosphor bronze, thickness=0.18mm
- 2.Surface finish: tin plated
- 3.Matched receptacle housing: TJC2509-2XnY
- 4.Applicable wires: CH-TJC2509-L AWG#24~AWG#20
CH-TJC2509-1-L AWG#28~AWG#26
- 5.Compliant to the current RoHS





CH-TJC2509-1-L	1.5	1.3	2.1	2.1
CH-TJC2509-L	2	1.6	2.9	2.9
Part.No	A	B	C	D
Dimension				

CUSTOMER DRAWING							Title: 2.5mm pitch WTB/WTW contact
Drawn	Heng.Yin	2022.7.9	Unit	Scale	Size	Edition	Part No.: CH-TJC2509-*L-**
Checked	Guoying.Wang	2022.7.9	mm	5:1	A4	B1	Previous part No.: /
			Sheet No. 1 Of 1				
Approved	Dongxu.Liu	2022.7.9	CWB				Specification No: PS4100

General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



Contact view
1:2











Notes:

- 1.Material: Phosphor bronze, thickness=0.2mm
- 2.Surface finish: Tin plaed
- 3.Matched receptacle housing: TJC2509-nAR, TJC2509-nARP
- 4.Applicable wires: CZ-TJC2509: AWG#26~ AWG#22
CZ-TJC2509-1: AWG#20
- 5.Compliant to the current RoHS

CZ-TJC2509-1	/	2.1	1.8	2.6	3.0
CZ-TJC2509	CZ-TJC2509-D	1.75	1.32	2.5	2.7
Part.No	Previous part No.	A	B	C	D
Dimension					

CUSTOMER DRAWING						Title: 2.5mm Pitch WTW pin contact
Drawn	Huan.Lu 2021.12.20	Unit	Scale	Size	Edition	Part No.: CZ-TJC2509-**-**
Checked	Guoying.Wang 2021.12.20	mm	5:1	A4	B	Part No.: CZ-TJC2509-D
		Sheet No. 1 Of 1				Document No.: CP-DWG-01443
Approved	Dongxu.Liu 2021.12.20	CWB				Specification No.: PS4100

	1	2	3	4	5	6	7	8	9	10				
A						General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date	A
							0~3	±0.13						
							3~18	±0.23						
							18~50	±0.35						
							≥50	±0.55						



Note:

1.Material

Wafer:PA66+GF UL94V-0 GWT 750℃

Post: Brass, tin plated

2.Matched housing: TJC2509-nY/TJC2509B-nY







3.Packaging: packing bag

4.Compliant to the current RoHS

15			TJC2509-15AK	TJC2509-15A	40.0	38.3	35.0
14			TJC2509-14AK	TJC2509-14A	37.5	35.8	32.5
13			TJC2509-13AK	TJC2509-13A	35.0	33.3	30.0
12			TJC2509-12AK	TJC2509-12A	32.5	30.8	27.5
11			TJC2509-11AK	TJC2509-11A	30.0	28.3	25.0
10			TJC2509-10AK	TJC2509-10A	27.5	25.8	22.5
9			TJC2509-9AK	TJC2509-9A	25.0	23.3	20.0
8			TJC2509-8AK	TJC2509-8A	22.5	20.8	17.5
7			TJC2509-7AK	TJC2509-7A	20.0	18.3	15.0
6			TJC2509-6AK	TJC2509-6A	17.5	15.8	12.5
5			TJC2509-5AK	TJC2509-5A	15.0	13.3	10.0
4	TJC2509-4AK-1	TJC2509-4A-1	TJC2509-4AK	TJC2509-4A	12.5	10.8	7.5
3	TJC2509-3AK-1	TJC2509-3A-1	TJC2509-3AK	TJC2509-3A	10.0	8.3	5.0
2	TJC2509-2AK-1	TJC2509-2A-1	TJC2509-2AK	TJC2509-2A	7.5	5.8	2.5
Ckts (n)	Part No.	Previous part No.	Part No.	Previous part No.	A	B	C
	With flange(Non universal type)		Without flange(General type)		Dimensions		

CUSTOMER DRAWING							Title: 2.5mm pitch WTB header	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: TJC2509-nAK-* * **.*	
			mm	2.5:1	A4	B1	Previous part No.: TJC2509-nA/TJC2509-nA-1	
Checked	Guoying.Wang	2022.3.16	Sheet No.		1 Of 1		Document No.: CP-DWG-01130	
Approved	Dongxu.Liu	2022.3.17	CWB				Specification No.: PS4100	

General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



16	TJC2509-16ADK	TJC2509-16AD	42.5	40.8	37.5
15	TJC2509-15ADK	TJC2509-15AD	40.0	38.3	35.0
14	TJC2509-14ADK	TJC2509-14AD	37.5	35.8	32.5
13	TJC2509-13ADK	TJC2509-13AD	35.0	33.3	30.0
12	TJC2509-12ADK	TJC2509-12AD	32.5	30.8	27.5
11	TJC2509-11ADK	TJC2509-11AD	30.0	28.3	25.0
10	TJC2509-10ADK	TJC2509-10AD	27.5	25.8	22.5
9	TJC2509-9ADK	TJC2509-9AD	25.0	23.3	20.0
8	TJC2509-8ADK	TJC2509-8AD	22.5	20.8	17.5
7	TJC2509-7ADK	TJC2509-7AD	20.0	18.3	15.0
6	TJC2509-6ADK	TJC2509-6AD	17.5	15.8	12.5
5	TJC2509-5ADK	TJC2509-5AD	15.0	13.3	10.0
4	TJC2509-4ADK	TJC2509-4AD	12.5	10.8	7.5
3	TJC2509-3ADK	TJC2509-3AD	10.0	8.3	5.0
2	TJC2509-2ADK	TJC2509-2AD	7.5	5.8	2.5
Ckts (n)	Part No.	Previous part No.	Dimensions		
			A	B	C

Note:

1.Material

Wafer: PA66+GF UL94V-0 GWT 750℃

Post: Brass, tin plated


2.Matched housing: TJC2509-nY/TJC2509B-nY


3.Packaging: packing bag


4.Compliant to the current RoHS


CUSTOMER DRAWING						Title: 2.5mm pitch WTB header	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: TJC2509-nADK *((***)
Checked	Guoying.Wang	2022.3.16	mm	2.5:1	A4	B1	Previous part No.: TJC2509-nAD
			Sheet No.		1 Of 1		Document No.: CP-DWG-01131
Approved	Dongxu.Liu	2022.3.17	CWB				Specification No.: PS4100

CUSTOMER DRAWING						Title: 2.5mm pitch WTB header
Drawn	Jiawei.Ni 2024.2.6	Unit	Scale	Size	Edition	Part No.: TJC2509B-2AD *((**.*))
Checked	Qu.Wang 2024.2.6	mm	2.5:1	A4	B0	Previous part No.: /
		Sheet No. 1 Of 1				
Approved	Dongxu.Liu 2024.2.6					
















General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



Assembly view
(TJC2509-nAR&TJC2509-nY)
(DIM FYI)



Assembly view
(TJC2509-nAR&TJC2509B-nY)
(DIM FYI)










Notes:

- 1.Material: PA66 UL94 V-0;
- 2.Matched plug housing: TJC2509-nY, TJC2509B-nY;
- 3.Matched lock plate: TJC2509B-nS;
- 4.Matched pin contact: CZ-TJC2509,CZ-TJC2509-1;
- 5.Packaging: Bag packaging;
- 6.Compliant to the current RoHS.

12	TJC2509-12AR	32.5	27.5	22.5
9	TJC2509-9AR	25	20	15
8	TJC2509-8AR	22.5	17.5	12.5
6	TJC2509-6AR	17.5	12.5	10
5	TJC2509-5AR	15	10	/
4	TJC2509-4AR	12.5	7.5	/
3	TJC2509-3AR	10	5.0	/
2	TJC2509-2AR	7.5	2.5	/
Ckts (N)	Part No.	A	B	C
		Dimension		

CUSTOMER DRAWING						Title: 25mm Pitch WTW receptacle housing
Drawn	Huan.Lu 2021.12.20	Unit	Scale	Size	Edition	Part No.: TJC2509-nAR(**-*)
Checked	Guoying.Wang 2021.12.20	mm	2:1	A4	A0	Previous part No.: /
		Sheet No. 1 Of 1				Document No.: CP-DWG-01446
Approved	Dongxu.Liu 2021.12.20	CWB				Specification No.: PS4100

General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13	△	／	Update the content,add 14Pin products	Huan.Lu	2022.8.17
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					






Ckts (N)	part No.	Previous part No.	Dimension				
			A	B	C	D	E
14	TJC2509-14ARP	/	37.5	32.5	27.5	37.9	41.2
12	TJC2509-12ARP	TJC2509-12AR-1	32.5	27.5	22.5	32.9	36.2
11	TJC2509-11ARP	TJC2509-11AR-1	30	25	20	30.4	33.7
10	TJC2509-10ARP	TJC2509-10AR-1	27.5	22.5	17.5	27.9	31.2
9	TJC2509-9ARP	TJC2509-9AR-1	25	20	15	25.4	28.7
8	TJC2509-8ARP	TJC2509-8AR-1	22.5	17.5	12.5	22.9	26.2
7	TJC2509-7ARP	TJC2509-7AR-1	20	15	10	20.4	23.7
6	TJC2509-6ARP	TJC2509-6AR-1	17.5	12.5	10	17.9	21.2
5	TJC2509-5ARP	TJC2509-5AR-1	15	10	/	15.4	18.7
4	TJC2509-4ARP	TJC2509-4AR-1	12.5	7.5	/	12.9	16.2
3	TJC2509-3ARP	TJC2509-3AR-1	10	5.0	/	10.4	13.7
2	TJC2509-2ARP	TJC2509-2AR-1	7.5	2.5	/	7.9	11.2

Notes:

- 1.Material: PA66 UL94 V-0;
- 2.Matched plug housing: TJC2509-nY, TJC2509B-nY;
- 3.Matched lock plate: TJC2509B-nS;
- 4.Matched pin contact: CZ-TJC2509,CZ-TJC2509-1;
- 5.Packaging: Bag packaging;
- 6.Compliant to the current RoHS.

CUSTOMER DRAWING						Title: 25mm Pitch WTW receptacle housing
Drawn	Huan.Lu 2021.12.20	Unit	Scale	Size	Edition	Part No.: TJC2509-nARP(**-*)
Checked	Guoying.Wang 2021.12.20	mm	2:1	A4	A0	Previous part No.: TJC2509-nAR-1
		Sheet No. 1 Of 1				Document No.: CP-DWG-01447
Approved	Dongxu.Liu 2021.12.20	CWB				Specification No.: PS4100

General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



Note:

1. Material

Wafer: PA66+GF UL94V-0 GWT 750°C


Post: Brass, tin plated


2. Matched housing: TJC2509-nY/TJC2509B-nY

3.Packaging: packing bag



4.Compliant to the current RoHS

CUSTOMER DRAWING						Title: 2.5mm pitch WTB Header	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: TJC2509-2AT(**-*)
Checked	Guoying.Wang	2022.3.16	mm	2:1	A4	B1	Previous part No.: TJC25054-2A
Approved	Dongxu.Liu	2022.3.17	Sheet No. 1 Of 1				Document No.: CP-DWG-01126
CWB						Specification No.: PS4100	





General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



Notes:

1.Material:

Standards: PA66 UL94V-0

Others: PA66 UL94V-0 GWT 750℃

2.Matched header: TJC2509 series header&receptacle housing

3.Matched retainer: TJC2509B-nS


4.Matched contact: CH-TJC2509/CH-TJC2509-1/CH-TJC2509-2


5.Packaging: packing bag


6.Compliant to the current RoHS

16	TJC2509B-16Y	42.3	40.65	37.5	32.5	5
15	TJC2509B-15Y	39.8	38.15	35.0	30.0	5
14	TJC2509B-14Y	37.3	35.65	32.5	27.5	5
13	TJC2509B-13Y	34.8	33.15	30.0	25.0	5
12	TJC2509B-12Y	32.3	30.65	27.5	22.5	5
11	TJC2509B-11Y	29.8	28.15	25.0	20.0	5
10	TJC2509B-10Y	27.3	25.65	22.5	17.5	5
9	TJC2509B-9Y	24.8	23.15	20.0	15.0	5
8	TJC2509B-8Y	22.3	20.65	17.5	12.5	5
7	TJC2509B-7Y	19.8	18.15	15.0	10.0	5
6	TJC2509B-6Y	17.3	15.65	12.5	10.0	5
5	TJC2509B-5Y	14.8	13.15	10.0	/	5
4	TJC2509B-4Y	12.3	10.65	7.5	/	5
3	TJC2509B-3Y	9.8	8.15	5.0	/	4.5
2	TJC2509B-2Y	7.3	5.65	2.5	/	3.9
Ckts (n)	Part No.	Dimensions				
		A	B	C	D	E


CUSTOMER DRAWING						Title: 2.5mm pitch WTB/WTW housing	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: TJC2509B-nY *(**~*)
Checked	Guoying.Wang	2022.3.16	mm	4:1	A4	B1	Previous part No.: /
			Sheet No.			1 Of 1	
Approved	Dongxu.Liu	2022.3.17	CWB				Specification No.: PS4100








General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



6	Gummed tape		
5	Packing box		112000PCS/box
4	Packing bag		112000PCS/bag
3	Packing reel		8000PCS/disc
2	Certificate		
1	CH-TJC2509	TJC2509	
	CH-TJC2509-1	TJC2509-1	
	CH-TJC2509-2	TJC2509-2	
Number	Part No.	Previous Part No.	Remarks

CUSTOMER DRAWING						Title: Packaging specification	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.: CH-TJC2509-x-xx
			mm	/	A4	B1	Previous part No.: TJC2509/TJC2509-x
Checked	Ji.Wu	2022.7.1	Sheet No.		1 Of 1		Document No.: BZ-DWG-00648
Approved	Dongxu.Liu	2022.7.1	CWB				Specification No.: PS4100/PS4169




General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



6	Gummed tape	
5	Packing box	88000PCS/box
4	Packing bag	88000PCS/bag
3	Packing reel	8000PCS/disc
2	Certificate	
1	CH-TJC2509-1-L	
	CH-TJC2509-L	
Number	Part No.	Remarks

CUSTOMER DRAWING							Title: Packaging specification	
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.:	CH-TJC2509-x-L-xx
			mm	/	A4	B0	Previous part No.:	/
Checked	Ji.Wu	2022.7.1	Sheet No.		1 Of 1		Document No.:	BZ-DWG-00648
Approved	Dongxu.Liu	2022.7.1	CWB				Specification No.:	PS4100/PS4169

General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					



6	Gummed tape	
5	Packing box	88000PCS/bag
4	Packing bag	88000PCS/bag
3	Packing reel	8000PCS/disc
2	Certificate	
1	CZ-TJC2509	
Number	Designation	Remarks


CUSTOMER DRAWING						Title: Packaging specification	
Drawn	Huan.Lu 2021.12.20	Unit	Scale	Size	Edition	Part No.: CZ-TJC2509-X-**	
Checked	Guoying.Wang 2021.12.20	mm	/	A4	B0	Previous part No.: /	
		Sheet No. 1 Of 1				Document No.: BZ-DWG-00790	
Approved	Dongxu.Liu 2021.12.20	CWB				Specification No.: PS4100	

	1	2	3	4	5	6	7	8	9	10				
A	Packing bag Sealed 3 2 1					General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date	A
							0~3	±0.13						
							3~18	±0.23						
							18~50	±0.35						
							≥50	±0.55						


	1	2	3	4	5	6	7	8	9	10				
A						General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date	A
							0~3	±0.13						
B							3~18	±0.23						
C							18~50	±0.35						
D							≥50	±0.55						
B														B
C														C
D														D
E														E
F														F
G														G
H														H

Packing bag

Sealed



Packing box



CWB RoHS

SIZE 470×325mm×340mm

ADDRESS ZHEJIANG SHENGYUE QINGSHI TEL:0574-62312253
HONGGANG ZHEN XINGFU DONG LU
1098 HAO HE JING GONGYE YUAN FAX:0574-62313682

5	Gummed tape	TJC2509-14ARP	/	/	/	500	
		TJC2509-12ARP	TJC2509-12AR-1	/	/	500	
		TJC2509-11ARP	TJC2509-11AR-1	/	/	500	
		TJC2509-10ARP	TJC2509-10AR-1	/	/	500	
		TJC2509-9ARP	TJC2509-9AR-1	TJC2509-12AR	/	500	
4	Packing box	TJC2509-8ARP	TJC2509-8AR-1	TJC2509-9AR	/	500	
		TJC2509-7ARP	TJC2509-7AR-1	TJC2509-8AR	/	500	
3	Packing bag	TJC2509-6ARP	TJC2509-6AR-1	TJC2509-6AR	/	500	
		TJC2509-5ARP	TJC2509-5AR-1	TJC2509-5AR	/	1000	
2	Certificate	TJC2509-4ARP	TJC2509-4AR-1	TJC2509-4AR	/	1000	
		TJC2509-3ARP	TJC2509-3AR-1	TJC2509-3AR	/	1000	
1	TJC2509 series plastic parts	TJC2509-2ARP	TJC2509-2AR-1	TJC2509-2AR	/	1000	
Number	Designation	Part No.	Previous part No.	Part No.	Previous part No.	Pcs/bag	Remarks


CUSTOMER DRAWING

Drawn	Huan.Lu 2021.12.20	Unit	Scale	Size	Edition
Checked	Guoying.Wang 2021.12.20	mm	/	A4	B0
Approved	Dongxu.Liu 2021.12.20	Sheet No.	1 Of 1		

Package specification

Part No.: TJC2509 Serise plug housing
Previous part No.: /
Document No.: BZ-DWG-00789
Specification No.: PS4100


CWB




General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13	△1	/	Add TJC2509-2X5AD,TJC2509-2X7AD products	Jiawei.Ni	2024.6.25
	3~18	±0.23	△2	/	Add TJC2509B-2X5AD products	Jiawei.Ni	2024.11.29
	18~50	±0.35	△3	/	Add TJC2509-2X6AD products	Jiawei.Ni	2025.5.14
	≥50	±0.55					

Packing bag

Sealed



Packing box




5	Gummed tape	TJC2509B-2X5AD	500	
4	Packing box	TJC2509-2X18AD	250	
3	Packing bag	TJC2509-2X17AD	250	
2	Certificate	TJC2509-2X14AD	250	
1	TJC2509(B)-2XnAD	TJC2509-2X11AD	250	
		TJC2509-2X10AD	500	
		TJC2509-2X9AD	500	
		TJC2509-2X7AD	500	
		TJC2509-2X6AD	500	
		TJC2509-2X5AD	500	
Number	Designation	Part No.	Pcs/bag	Remarks


CUSTOMER DRAWING						Title: Packaging specification	
Drawn	heng.Yin 2022.7.9	Unit	Scale	Size	Edition	Part No.:	TJC2509(B)-2XnAD- *(***)
Checked	Guoying.Yin 2022.7.9	mm	/	A4	B3	Previous part No.:	/
		Sheet No. 1 Of 1				Document No.:	BZ-DWG-00874
Approved	Dongxu.Liu 2022.7.9	CWB				Specification No.:	PS4100

Packing bag

Sealed



Packing box



General Tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13					
	3~18	±0.23					
	18~50	±0.35					
	≥50	±0.55					


5	Gummed tape	TJC2509-16Y	500	
4	Packing box	TJC2509-15Y	500	
3	Packing bag	TJC2509-14Y	500	
2	Certificate	TJC2509-13Y	500	
1	TJC2509 series plastic parts	TJC2509-12Y	1000	
Number	Designation	TJC2509-11Y	1000	
		TJC2509-10Y	1000	
		TJC2509-9Y	1000	
		TJC2509-8Y	1000	
		TJC2509-7Y	1000	
		TJC2509-6Y	1000	
		TJC2509-5Y	1000	
		TJC2509-4Y	1000	
		TJC2509-3Y	1000	
		TJC2509-2Y	1000	

CUSTOMER DRAWING						Title: Packaging specification		
Drawn	Heng.Yin	2022.3.16	Unit	Scale	Size	Edition	Part No.:	TJC2509 series housing
Checked	Guoying.Wang	2022.3.16	mm	/	A4	B1	Previous part No.:	/
Approved	Dongxu.Liu	2022.3.17	Sheet No.	1 Of 1			Document No.:	CP-DWG-00809
							Specification No.:	PS4100


General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13			New model TJC2509-2X5Y	Jiawei.Ni	2024.3.4
	3~18	±0.23			New model TJC2509-2X7Y	Jiawei.Ni	2024.6.25
	18~50	±0.35					
	≥50	±0.55					

Packing bag

Sealed



Packing box




5	Gummed tape	TJC2509-2X18Y	300	
4	Packing box	TJC2509-2X17Y	300	
3	Packing bag	TJC2509-2X14Y	300	
2	Certificate	TJC2509-2X11Y	300	
1	TJC2509-2XnY	TJC2509-2X10Y	300	
Number	Designation	TJC2509-2X9Y	300	
		TJC2509-2X7Y	300	
		TJC2509-2X5Y	300	
		Part No.	Pcs/bag	Remarks

CUSTOMER DRAWING						Title: Packaging specification	
Drawn	heng.Yin 2022.7.9	Unit	Scale	Size	Edition	Part No.:	TJC2509-2XnY(**-*)
Checked	Guoying.Yin 2022.7.9	mm	/	A4	B2	Previous part No.:	/
Approved	Dongxu.Liu 2022.7.9	Sheet No.	1 Of 1			Document No.:	BZ-DWG-00873
						Specification No.:	PS4100


General tolerance	Dimension	Tolerance	Rev. No	Location	Description	Reviser	Date
	0~3	±0.13			New model TJC2509-2X5YS	Jiawei.Ni	2024.3.4
	3~18	±0.23			New model TJC2509-2X7YS,9YS	Jiawei.Ni	2024.6.25
	18~50	±0.35			New model TJC2509-2X10YS	Jiawei.Ni	2024.7.3
	≥50	±0.55					

Packing bag

Sealed



Packing box



TJC2509-2X10YS	/	400	
TJC2509-2X9YS	/	400	
TJC2509-2X7YS	/	500	
TJC2509-2X5YS	/	500	
TJC2509B-16S	TJC2509B-16YS	1000	
TJC2509B-15S	TJC2509B-15YS	1000	
TJC2509B-14S	TJC2509B-14YS	1000	
TJC2509B-13S	TJC2509B-13YS	1000	
TJC2509B-12S	TJC2509B-12YS	1000	
TJC2509B-11S	TJC2509B-11YS	1000	
TJC2509B-10S	TJC2509B-10YS	1000	
TJC2509B-9S	TJC2509B-9YS	1000	
TJC2509B-8S	TJC2509B-8YS	1000	
TJC2509B-7S	TJC2509B-7YS	1000	
TJC2509B-6S	TJC2509B-6YS	1000	
TJC2509B-5S	TJC2509B-5YS	1000	
TJC2509B-4S	TJC2509B-4YS	1000	
TJC2509B-3S	TJC2509B-3YS	1000	
TJC2509B-2S	TJC2509B-2YS	1000	
Part No.	Previous part No.	Pcs/bag	Remarks

5	Gummed tape
4	Packing box
3	Packing bag
2	Certificate
1	TJC2509 series Retainer
Number	Designation

CUSTOMER DRAWING						Title: Packaging specification	
Drawn	Huan.Lu 2021.8.26	Unit	Scale	Size	Edition	Part No.: TJC2509-nS/2XnYS	
		mm	/	A4	B3	Previous part No.: /	
Checked	Qu.Wang 2021.8.26	Sheet No.		1 Of 1		Document No.: BZ-DWG-00647	
Approved	Dongxu.Liu 2021.8.26					Specification No.: PS4100	


TJC2509 系列命名规则

TJC2509 series naming conventions

1. Contact

CH-TJC2509-**-*, CZ-TJC2509-**-*, CH-TJC2509-L-**-*


CH - TJC2509 - * - L - * *



2. Housing


TJC2509(B)-nY*(**-*), TJC2509-2×nY(**-*)

TJC2509 B -2× n Y * (WT * -*)



3. TJC2509-nARP (**-*)


TJC2509— n AR P (** -*)



4. Retainer

TJC2509(B)—nS *(**-*) , TJC2509—2×nYS *(**-*)

TJC2509 B—2×n S *(WT * -*)



TJC2509-nAK **(***-*)**, TJC2509-nAWJ **(***-*)**, TJC2509-nAWJDK **(***-*)**, TJC2509-nADK **(***-*)**, TJC2509B-nAD **(***-*)**, TJC2509-nAT **(***-*)**, TJC2509E-5AWJDK, TJC2509-2×nAD **(***-*)**, TJC2509B-2×5AD **(***-*)**

Series name

↓

Flammability: None...UL94V-0

Material: 1...PA66+GF

Color: NL...Natural, BK...Black, GN...Green, BL...Blue,
RD...Red, YW...Yellow, BN...Brown, VT...Violet, PN...Pink,
OG...Orange, DGN...Dark Green, DBL...Dark Blue,
DRD...Dark Red, DYW...Dark Yellow, DOG...Dark Orange

Glow wire: GW...GWT 750°C

Special structure mark

Structure mark: None...Standard, D...With boss, J...With PCB
stabilizer, T...Taping type, K...With kink

Installation direction: None...Top entry type, W...Side entry type

Product category: A...Header

No. of circuits in each row

Number of rows: None...Single row, 2×...Two rows

Structure: None...standard parts, E...nonstandard part , B...nonstandard part

TJC2509-nAKmZ(a.b...) * (**-*), TJC2509-nADKmZ(a.b...) * (**-*),
TJC2509-nAWJKmZ(a.b...) * (**-*), TJC2509-nAWJDKmZ(a.b...) * (**-*),
TJC2509-nATmZ(a.b...) * (**-*)

Missing circuit number: "a.b..." ...The positive integer represents the position of the missing circuits

No. of actual circuits: mZ ("m" is positive integer)

Product category: A...Header

No. of circuits: ADK...2~16, AK...2~15, others...2~4

Part No.	Circuit No.														
	○:with post; ×:without post														
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
...13A ... 7Z(2.3.5.7.9.11)...	○	×	×	○	×	○	×	○	×	○	×	○	○		
...4A ... 3Z(2)...	○	×	○	○											
.....															